



Monitors galore from TSL



View with confidence: the 3G V series AVMU2-3G

Making its European debut on TSL's stand you'll find a new monitor capable of decoding all standards up to and including 1080p50. The 3G V series (AVMU2-3G) includes precision HD/SDI audio metering with an integrated 4.75-inch, 16.9 LCD screen for professional broadcast applications.

Not to be outdone, TSL's Monitor Plus Audio family is also taking its European bow. This comprises four rack mount confidence monitors with passive, active, analogue and AES digital options. Designed by John Watkinson, the units deliver outstanding sound quality at a price that will suit the wider broadcast market, says TSL.

Alongside those beauties is TSL's first showing, in Europe at least, of its Power Manager Mains Distribution Units (MDU). The series four units comprise: Power Manager for intelligent power distribution with Ethernet SNMP alarms, e-mail alerts and latching relays; Power Alert, featuring Ethernet SNMP alarms; Power Change Over, which has dual input auto changeover and 14 way fused outlets; and the entry level Power Standard.

TSL's 3G HD 1080p (50Hz) and Dolby decoding rack-mount audio monitor AMU1-3G is its latest multi-standard, multi-formatted rack mount audio product. The unit has been designed to fulfil a requirement for comprehensive, intuitive and compact metering of Dolby E bit streams from HD/SDI video formats up to and including 1080p50.

Also featured is the established 8-channel HD/SDI and Dolby decoding rack audio monitor which provides a complete HD monitoring solution for master control rooms, play-out, production, lines and outside broadcast requirements.